DRILLER: REMOVE COPY AND RETAIN FOR YOUR RECORDS. RETURN COUNTY COPY TO COUNTY ENVIRONMENTAL AGENCY. SUBMIT COPY TO OWNER. RETURN ALL OTHER PARTS TO DEPARTMENT OF ENVIRONMENT, 1800 WASHINGTON BOULEVARD • BALTIMORE, MARYLAND 21230

C 1 9831 SEQUENCE NO. (MDE USE ONLY)	STATE OF MARYLAND WELL COMPLETION REPORT	THIS REPORT MUST BE SUBMITTED WITHIN 45 DAYS AFTER WELL IS COMPLETED.
1 2 3 6 (THIS NUMBER IS TO BE PUNCHED IN COLS. 3-6 ON ALL CARDS)	FILL IN THIS FORM COMPLETELY PLEASE TYPE	COUNTY NUMBER
ST/CO USE ONLY DATE WELL COM DATE Received MM DO YY MM DO	PLETED Depth of Well	PERMIT NO. FROM "PERMIT TO DRILL WELL"
8 13 15	20 (TO NEAREST FOOT)	28 29 30 31 32 33 34 35 36 37
OWNER		
SUBDIVISION SECTION LOT		
WELL LOG	GROUTING RECORD yes no	C 3
Not required for driven wells	WELL HAS BEEN GROUTED (Circle Appropriate Box)	1 2 PUMPING TEST
STATE THE KIND OF FORMATIONS PENETRATED, THEIR COLOR, DEPTH, THICKNESS AND IF WATER BEARING DESCRIPTION (Use FEET Chine	CEMENT CM BENTONITE CLAY BC	HOURS PUMPED (nearest hour)
additional sheets if needed) FROM TO bear		PUMPING RATE (gal. per min.)
	GALLONS OF WATER DEPTH OF GROUT SEAL (to nearest foot)	METHOD USED TO MEASURE PUMPING RATE
	from $\frac{1}{48}$ TOP 52 ft. to $\frac{1}{54}$ BOTTOM 58 ft.	WATER LEVEL (distance from land surface)
	(enter 0 if from surface) casing CASING RECORD	BEFORE PUMPING ft.
	types insert ST CO	17 20 tt.
	(appropriate code below PLOT	WHEN PUMPING         22         25         ft.           TYPE OF PUMP USED (for test)
	PLASTIC OTHER	A air P piston T turbine
	MÅIN Nominal diameter Total depth CASING top (main) casing of main casing TYPE (nearest inch)! (nearest foot)	Z7 Z7 other C centrifugal R rotary O (describe
	<u> </u>	27   27   27   below)     J jet   S submersible
	E OTHER CASING (if used) A diameter depth (feet)	
	A diameter depth (feet) C inch from to C	PUMP INSTALLED
	A	DRILLER INSTALLED PUMP YES NO (CIRCLE) (YES or NO)
		IF DRILLER INSTALLS PUMP, THIS SECTION MUST BE COMPLETED FOR ALL WELLS.
	screen type or open hole ST BR HO	TYPE OF PUMP INSTALLED PLACE (A,C,J,P,R,S,T,O) 29
	appropriate STEEL BRASS OPEN BRONZE HOLE	IN BOX 29. CAPACITY:
		GALLONS PER MINUTE (to nearest gallon) 31 35
		PUMP HORSE POWER
NUMBER OF UNSUCCESSFUL WELLS:	DEPTH (nearest ft.)	PUMP COLUMN LENGTH (nearest ft.)
WELL HYDROFRACTURED	$E \frac{1}{8} \frac{1}{9} \frac{11}{11} \frac{15}{17} \frac{17}{21}$	CASING HEIGHT (circle appropriate box and enter casing height)
	C 2 H 2 23 24 26 30 32 36	
A A WELL WAS ABANDONED AND SEALED WHEN THIS WELL WAS COMPLETED E ELECTRIC LOG OBTAINED	S C 3 R 38 39 41 45 47 51	below (nearest) foot)
E ELECTRIC LOG OBTAINED P TEST WELL CONVERTED TO PRODUCTION WELL	R 38 39 41 45 47 51 E E SLOT SIZE 1 2 3	49 50 51 A LOCATION OF WELL ON LOT
I HEREBY CERTIFY THAT THIS WELL HAS BEEN CONSTRUCTED ACCORDANCE WITH COMAR 26.04.04 "WELL CONSTRUCTION" AN IN CONFORMANCE WITH ALL CONDITIONS STATED IN THE ABO	N DIAMETER (NEAREST	SHOW PERMANENT STRUCTURE SUCH AS BUILDING, SEPTIC TANKS, AND /OR
IN COMPONENTIACE WITH ALL CONDITIONS STATED IN THE ABO CAPTIONED PERMIT, AND THAT THE INFORMATION PRESENT HEREIN IS ACCURATE AND COMPLETE TO THE BEST OF N KNOWLEDGE.	56 60	LANDMARKS AND INDICATE NOT LESS THAN TWO DISTANCES
DRILLERS LIC. NO. 1 M _ D 1	GRAVEL PACK	(MEASUREMENTS TO WELL)
	IF WELL DRILLED WAS FLOWING WELL INSERT F IN BOX 68 68	
DRILLERS SIGNATURE (MUST MATCH SIGNATURE ON APPLICATION)	MDE USE ONLY (NOT TO BE FILLED IN BY DRILLER)	
LIC. NO.1 D I	T (E.R.O.S.) W Q	
SITE SUPERVISOR (sign. of driller or journeyman	70 72 74 75 76	₩
responsible for sitework if different from permittee)	TELESCOPE LOG 74 75 76 CASING INDICATOR OTHER DATA	

ORIGINAL